

# AZTRA UNDER COUNTER TECHNICAL DATASHEET

## AZ5CT AZTRA ONE DOOR UNDER-COUNTER



## AZ10CT AZTRA TWO DOOR UNDER-COUNTER



## AZ5UC AZTRA ONE DOOR UNDER-COUNTER



### AZ5CT

Dimensions (mm)	External	Internal
Width	455	375
Depth	734	583
Height	870	460
Door Opening		375
<b>Capacity</b>		
Capacity cu.ft/ltrs		3.8/109

### AZ10CT

Dimensions (mm)	External	Internal
Width	885	805
Depth	734	533
Height	870	460
Door Opening		358
<b>Capacity</b>		
Capacity cu.ft/ltrs		8.3/234

### AZ5UC

Dimensions (mm)	External	Internal
Width	660	580
Depth	609	443
Height	830	460
Door Opening		580
<b>Capacity</b>		
Capacity cu.ft/ltrs		4.6/131

## KEY FEATURES

- Foodsafe stainless steel exterior and interior base, with aluminium interior walls
- Integral 'easy grab' door handle
- Self closing doors
- Magnetic balloon door gaskets with 100% tight seal
- Fitted with 2 of 1/1GN nylon coated wire shelves per section as standard or trayslides to accommodate 1/1GN containers
- Anti-tilt trayslides
- Removable racking system
- Castors to rear, adjustable feet to front for cabinet stability
- Precision injected, high density 75mm polyurethane insulation with low GWP (Global Warming Potential) and zero ODP (Ozone Depletion Potential)
- CoolSmart controller
- Designed and engineered to operate efficiently up to 43°C ambient
- Front vented refrigeration system for excellent performance
- Fully automatic air cooled condensing unit
- Defrost water is vaporised using recycled heat from compressor
- High performance helium leak testing

## OPTIONS

- Stainless steel interior
- Additional shelving / trayslides
- Two drawers available on AZ5UC , including freezer (L) model
- Left door hang
- Hydrocarbon versions



# AZTRA UNDER COUNTER TECHNICAL DATA

	HAZ5UC	LAZ5UC	HAZ5CT	LAZ5CT	HAZ10CT	LAZ10CT
Temperature (°C)	+1/+4°C	-18/-22°C	+1/+4°C	-18/-22°C	+1/+4°C	-18/-22°C
Climate Class	Class 4 (30°C)	Class 4 (30°C)	Class 4 (30°C)	Class 4 (30°C)	Class 4 (30°C)	Class 4 (30°C)
Power Supply	230V/50Hz/1Ph					
Fuse (Amps)	13	13	13	13	13	13
Defrost	Automatic Off Cycle	Automatic Hot Gas	Automatic Off Cycle	Automatic Hot Gas	Automatic Off Cycle	Automatic Hot Gas
Noise level (dBA)	55	61	55	61	59	61

## Fittings

Shelves	2	2	2	2	4	4
Trayslides per door	4	4	4	4	4	4

## Electrical / Energy Data - Standard Refrigerant

	R134a	R404A	R134a	R404A	R134a	R404A
Refrigerant	R134a	R404A	R134a	R404A	R134a	R404A
Energy Efficiency Class	B	D	B	D	C	D
Energy Consumption (kW / 24hrs)	1.53	4.28	1.45	3.93	2.12	6.33
Start Up (Amps)	8.7	11.6	8.7	11.6	9.6	16.6
Running (Amps)	1.44	1.78	1.52	1.78	1.6	1.95
Heat Rejection	285	298	285	298	407	589

## Electrical / Energy Data - Hydrocarbon Refrigerant

	R290	R290	R290	R290	R290	R290
Refrigerant	R290	R290	R290	R290	R290	R290
Energy Efficiency Class	B	D	A	C	C	D
Energy Consumption (kW / 24hrs)	1.50	4.10	1.22	3.75	2.15	5.94
Start Up (Amps)	9.5	14.2	9.5	14.2	9.5	14.2
Running (Amps)	1.73	2.46	1.44	2.46	1.83	2.59
Heat Rejection	484	623	484	623	484	623

## IMPORTANT NOTES:

\*Energy consumption is tested to EN16825 in 24hrs

\*\*Heat rejection is evaporating at -10°C in 32°C Ambient

All refrigeration equipment requires adequate ventilation for efficient and effective performance

Williams is committed to a policy of continual product development and innovation. As such, we reserve the right to change product specifications stated without prior notice.

Williams Refrigeration  
Bryggen Road,  
North Lynn Industrial Estate  
King's Lynn, Norfolk. PE30 2HZ

T +44(0) 1553 817 000  
Spares: +44(0) 1553 817 017  
E info@williams-refrigeration.co.uk  
W www.williams-refrigeration.co.uk

