

SmartStore Range

Model: SmartStore Packaged Modular Rooms - Datasheet



Key Features

- Foodsafe powder coated exterior and interior finish
- Modular construction facilitates installation in areas with restricted access
- CoolSmart controller is designed for easy operation and features clear digital display
- Designed and engineered to operate efficiently up to a 32°C ambient, this exceeds Climate Class 4
- Front mounted refrigeration system for easy installation and service
- Precision injected, high density 90mm polyurethane insulation. Provides excellent thermal efficiency with low GWP (Global Warming Potential) and zero ODP (Ozone Depletion Potential)
- Available in a range of temperatures to store general produce, meat and frozen food
- Door heater cable for frozen food and meat storage models

- Fitted with lock for security and internal release mechanism for added safety
- Can be connected to a Williams temperature monitoring TAB system

Options

Variant	Temp	Storage
---------	------	---------

HSS	+1/+4°C	General Produce
MSS	-2/+2°C	Meat
LSS	-18/-22°C	Frozen Food

Dimensions

	HSS	MSS	LSS
External (mm):	H2180 W1300 / 1500 / 1750 / 2000 / 2250 / 2500 / 2750 / 3000 D1250 / 1500 / 1750 / 2000 / 2250 / 2500 / 2750 / 3000	H2180 W1300 / 1500 / 1750 / 2000 / 2250 / 2500 / 2750 / 3000 D1250 / 1500 / 1750 / 2000 / 2250 / 2500 / 2750 / 3000	H2180 W1300 / 1500 / 1750 / 2000 / 2250 / 2500 / 2750 / 3000 D1250 / 1500 / 1750 / 2000 / 2250 / 2500 / 2750 / 3000
Door Opening (mm):	Models 1312 - 1330 = D702 Models 1512 - 1530 = D842 Models 1712 - 2220 = D932 Models 2512 - 3015 = D932	Models 1312 - 1330 = D702 Models 1512 - 1530 = D842 Models 1712 - 2220 = D932 Models 2512 - 3015 = D932	Models 1312 - 1330 = D702 Models 1512 - 1530 = D842 Models 1712 - 2220 = D932 Models 2512 - 3015 = D932
Packed:	SmartStore rooms are packed on 2 pallets (pod system maybe on 3rd), however precise dimensions / weight will be given upon completion of product and shipping notice.		

Important Information

	HSS	MSS	LSS
Construction			
Exterior	0.7mm white PVC coated galvanised steel	0.7mm white PVC coated galvanised steel	0.7mm white PVC coated galvanised steel
Interior	0.7mm white PVC coated galvanised steel	0.7mm white PVC coated galvanised steel	0.7mm white PVC coated galvanised steel
Door	0.7mm white PVC coated galvanised steel	0.7mm white PVC coated galvanised steel	0.7mm white PVC coated galvanised steel
Power Supply	220V/240V 50Hz/1Ph 13 amp plug	220V/240V 50Hz/1Ph 13 amp plug	220V/240V 50Hz/1Ph 13 amp plug
Power Input			
Start Up	19.7 amps	26.7 amps	40 amps
Running	4.8 amps	6.18 amps	5.9 amps
Compressor HP	1/2	3/4	1 1/2
Energy Consumption (Tested to EN153) in 24hrs	?kW	?kW	?kW
Heat Rejection (Evaporating at -10°C in 32°C ambient)	1100 watts	1660 watts	3188 watts
Refrigerant	R134a	R134a	R404a
Defrost	Auto off cycle	Hot gas	Hot gas
Insulation ODP Zero Polyurethane	90mm	90mm	90mm
Noise Output	?dBA	?dBA	?dBA



Bryggen Road, North Lynn Industrial Estate
King's Lynn, Norfolk PE30 2HZ
T +44 (0) 1553 817000
F +44 (0) 1553 817111
Spares +44 (0)1553 817017
E info@williams-refrigeration.co.uk
W www.williams-refrigeration.com