

CRYSTAL MODULAR RETARDER PROVER

TECHNICAL DATASHEET

RPMC1T CRYSTAL RETARDER PROVER

RPMC2T CRYSTAL RETARDER PROVER

RPMC1T

Dimensions (mm)	External	Internal
Width	750	570
Depth	1000	780
Height	2160	1625
Door Opening		1650
Capacity		trays
Capacity (18X30" trays)		20

RPMC2T

Dimensions (mm)	External	Internal
Width	1500	1320
Depth	1000	820
Height	2160	1625
Door Opening		
Capacity		trays
Capacity (18X30" trays)		40

KEY FEATURES

- Foodsafe stainless steel exterior and interior
- State of the art control panel with easy to read LED display for temperature control and diagnostics
- Designed and engineered to operate efficiently up to a 43°C ambient
- Self closing doors
- Precision injected, high density 90mm polyurethane insulation.
- Provides excellent thermal efficiency with low GWP (Global Warming Potential) and zero ODP (Ozone Depletion Potential)
- Top mounted removable refrigeration system for easy servicing



CRYSTAL RETARDER PROVER TECHNICAL DATA

Crystal Retarder Prover	RPMC1T	RPMC2T
Temperature Retard (°C)	-5/+3°C	-5/+3°C
Temperature Prove (°C)	+38/+40°C	+38/+40°C
Power Supply	220V/240V 50Hz/1Ph	220V/240V 50Hz/1Ph
Fuse (Amps)	20	25
Defrost	Auto Electric	Auto Electric

Fittings

Trayslides	20	40
------------	----	----

Electrical Data - Standard Refrigerant

Refrigerant	R134a	R134a
Start Up (Amps)	19.7	20.5
Running (Amps)	17.4	20.5

IMPORTANT NOTES:

Williams is committed to a policy of continual product development and innovation. As such, we reserve the right to change product specifications stated without prior notice.

Williams Refrigeration
Bryggen Road,
North Lynn Industrial Estate
King's Lynn, Norfolk. PE30 2HZ

T +44(0) 1553 817 000
Spares: +44(0) 1553 817 017
E info@williams-refrigeration.co.uk
W www.williams-refrigeration.co.uk

