




Side Elevation
(Ventilation Space)



Side Elevation
(Shelving Heights)



Front Elevation



WILLIAMS REFRIGERATION RETAIN COPYRIGHT ON THIS DRAWING.
DO NOT SCALE FROM DRAWING. USE MARKED DIMENSIONS.
WILLIAMS REFRIGERATION ARE TO BE NOTIFIED OF ANY DISCREPANCIES IMMEDIATELY.

Multideck requires a minimum ventilation void of 100mm behind and above unit for heat to escape.

Electrical supply: 1 Phase
13amp UK standard plug top

Multideck Features	
<input checked="" type="checkbox"/> W	Write Finish
<input checked="" type="checkbox"/> S	Mirror Stainless Finish
<input checked="" type="checkbox"/> C	Castors
<input checked="" type="checkbox"/> F	Feet (For Remote Units Only)
<input checked="" type="checkbox"/> N	Nightblind
<input checked="" type="checkbox"/> S	Security Shutter
<input checked="" type="checkbox"/> RE	Remote Refrigeration Unit
Only checked features are included	

Multideck Options	
<input checked="" type="checkbox"/> SH	Additional Shelf
<input checked="" type="checkbox"/> SNB	Snack Basket (Hook On)
<input checked="" type="checkbox"/> TS	Tray Slide
<input checked="" type="checkbox"/> SRD	Solid Rear Loading Doors
<input checked="" type="checkbox"/> GRD	Glass Rear Loading Doors
<input checked="" type="checkbox"/> MT	Meat Temperature
<input checked="" type="checkbox"/> RAL	Coloured Finish (RAL)
<input checked="" type="checkbox"/> AV	Alternative Voltage
Only checked options are included	

Maximum operating ambient temperature +25 deg.c,
(climate class 3).
Manufacturing dimensional tolerance +/- 3mm.



Client:

Standard Product

Project:

Standard Product

Title:

R150-SCS R1 - R Series Multideck
Security Shutter Model
Mirror Stainless Finish

Drawn By:

PPR

DWG No:

R150-SCS R1

REV:

B

Williams Refrigeration Southern

T: +44 (0) 1862 835525

F: +44 (0) 1862 835526

E: estimating@williams-southern.co.uk

Kent, TN12 9BE

Standard Product