

CRYSTAL BAKERY CABINETS TECHNICAL DATASHEET



	RPC1T		RPC2T		PC1T		PC2T		C1MP20	
Dimensions (mm)	External	Internal	External	Internal	External	Internal	External	Internal	External	Internal
Width	737	587	1400	1250	737	587	1400	1250	737	587
Depth	941	800	941	800	941	800	941	800	941	800
Height	2140	1390*	2140	1550	2140	1550	2140	1550	2140	1503
Door Opening	1636		1636		1636		1636		1636	
Capacity										
Capacity Trays 18X30"	17		40		17		40		19	

*Due to blower plate

KEY FEATURES

- Foodsafe stainless steel exterior and interior
- State of the art control panel with easy to read LED display for temperature control and diagnostics**
- Designed and engineered to operate efficiently up to a 43°C ambient
- Self closing doors minimises temperature gain, reducing energy consumption
- Precision injected, high density 75mm polyurethane insulation.

- Provides excellent thermal efficiency with low GWP (Global Warming Potential) and zero ODP (Ozone Depletion Potential)
- Top mounted removable refrigeration system for easy servicing**
- Heavy duty, non-marking swivel castors with brakes – designed for ease of positioning
- Barrel locked doors for added security

OPTIONS

- Additional trayslides (18x30" - 2 slides)
- Stainless steel back
- Metric tray kit (600 x 400)

**RPC Only



CRYSTAL BAKERY CABINETS TECHNICAL DATA

Crystal Bakery Cabinets	RPC1T	RPC2T	PC1T	PC2T	C1MP20
Temperature (°C)	-5/+3°C Retard +38/+40°C Prove	-5/+3°C Retard +38/+40°C Prove	+38/+40	+38/+40	+38/+40
Power Supply	220V/240V 50Hz/1Ph				
Fuse (Amps)	20	25	20	25	13
Defrost	Auto Electric	Auto Electric	N/A	N/A	Auto Off -Cycle
Noise Level (dBA)	58	61	46	46	-

Fittings

Trayslides	34	80	34	80	38
------------	----	----	----	----	----

Electrical Data - Standard Refrigerant

Refrigerant	R134a	R134a	N/A	N/A	N/A
Start Up (Amps)	19.7	21	N/A	N/A	N/A
Running (Amps)	17.5	21	17	21	9.5
Heat Rejection (kW / 24hrs)*	1105	1105	N/A	N/A	N/A

IMPORTANT NOTES:

**Heat rejection is evaporating at -10°C in 32°C Ambient

If specialist artisan proving is to be carried out, the data shown here may be affected. Please contact Williams Refrigeration for further information.

Retarder Provers require water supply and drain, not supplied by Williams Refrigeration.

Williams is committed to a policy of continual product development and innovation. As such, we reserve the right to change product specifications stated without prior notice.

Williams Refrigeration
Bryggen Road,
North Lynn Industrial Estate
King's Lynn, Norfolk. PE30 2HZ

T +44(0) 1553 817 000
Spares: +44(0) 1553 817 017
E info@williams-refrigeration.co.uk
W www.williams-refrigeration.co.uk

