

# M-SERIES MULTIDECK - SECURITY SHUTTER

## TECHNICAL DATASHEET



M70-CS

M100-CS

M125-CS

M150-CS

M180-CS

### Dimensions (mm)

	M70-CS	M100-CS	M125-CS	M150-CS	M180-CS
Width	710	960	1250	1510	1856
Depth	850	850	850	850	850
Height	2052	2052	2052	2052	2052
Total Display Area (m <sup>2</sup> )	1.32	1.87	2.48	3.02	3.74

### Capacity

	M70-CS	M100-CS	M125-CS	M150-CS	M180-CS
Capacity (ltrs / cu.ft.)	322 / 11.4	458 / 16.2	607 / 21.4	740 / 26.1	916 / 32.4
Capacity (330ml cans)	252	364	476	588	736

## KEY FEATURES

- Security Shutter
- Large capacity
- Designed and engineered to operate efficiently up to 25°C ambient
- Innovative, energy saving aerofins, double as ticket strips
- Ceiling mounted LED strip lighting
- R452A refrigerant
- Double wheel castors
- Adjustable shelving

## OPTIONS

- Night Blind
- Sliding front doors
- Hinged front doors
- Chrome, impulse snack basket
- Additional shelving (White or Stainless)
- Undershelf LED strip lighting to all shelves
- Food tray slide
- Solid or glass rear loading doors
- Enhanced panoramic glass ends
- Choice of RAL coloured finishes
- Chameleon wrap
- Remote refrigeration system
- Multiplexed units
- Meat temperature



## GEM M-SERIES MULTIDECKS TECHNICAL DATA

M Series Security Shutter	M70-CS	M100-CS	M125-CS	M150-CS	M180-CS
Temperature (°C)	+3/+5°C	+3/+5°C	+3/+5°C	+3/+5°C	+3/+5°C
Climate Class	3	3	3	3	3
Power Supply	230V/50Hz/1Ph				
Fuse (Amps)	13	13	13	13	13
Defrost					
Noise level (dBA)	52	56	61	60	63.5
Weight	225	255	285	310	350
<b>Fittings</b>					
Shelves	4	4	4	4	4
Shelf Size (w x d)	640 x 390	890 x 390	1180 x 390	1440 x 390	1780 x 390
Base Size (w x d)	595 x 540	890 x 540	1180 x 540	1440 x 540	1785 x 540
<b>Electrical / Energy Data</b>					
Refrigerant	R452A	R452A	R452A	R452A	R452A
Energy Efficiency Index (EEI)					
Energy Consumption (kW / 24hrs)	10.7	11.6	13.8	17.3	20.5
Power Rating (W)	980	1028	1160	1376	1330

### IMPORTANT NOTES:

Williams is committed to a policy of continual product development and innovation. As such, we reserve the right to change product specifications stated without prior notice.

All refrigeration equipment requires adequate ventilation for efficient and effective performance.

Williams Refrigeration  
Bryggen Road,  
North Lynn Industrial Estate  
King's Lynn, Norfolk. PE30 2HZ

T +44(0) 1553 817 000  
Spares: +44(0) 1553 817 017  
E info@williams-refrigeration.co.uk  
W www.williams-refrigeration.co.uk

