

CHEFS DRAWERS TECHNICAL DATASHEET

WCD1 CHEFS DRAWERS



WCD1

Dimensions (mm)	External	Internal
Width	880	677
Depth	850	522
Height	475	268
Drawer Opening	1360	

Capacity

Capacity cu.ft/ltrs	3.3/94
---------------------	--------

KEY FEATURES

- Large capacity drawer size 2 x 1 GN (150mm maximum depth)
- Stacking capability for convenient refrigerator / freezer combination
- Removable refrigeration system designed for easy on-site service and maintenance
- Environmental friendly R290 natural refrigerant has a low GWP / zero ODP
- Foodsafe stainless steel exterior and interior
- Heavy duty, low level, non-marking swivel castors with brakes
- Magnetic balloon door gaskets with 100% tight seal
- CoolSmart controller
- Precision injected, high density polyurethane insulation with low GWP (Global Warming Potential) and zero ODP (Ozone Depletion Potential)
- Designed and engineered to operate efficiently up to a 43°C ambient.
- High performance helium leak testing

OPTIONS

- Heavy duty, high level castors with brakes (when suiting with prime cooking stations)
- Adjustable legs in lieu of castors (when suiting with prime cooking stations)
- Helicoil cable



CHEFS DRAWERS TECHNICAL DATA

Chef Drawers	HWCD1	LWCD1
Temperature (°C)	+1/+4°C	-18/-22°C
Climate Class	Class 4 (30°C)	Class 4 (30°C)
Power Supply	230V/50Hz/1Ph	230V/50Hz/1Ph
Fuse (Amps)	13	13
Defrost	Automatic Off Cycle	Automatic Hot Gas
Noise level (dBA)	59	41

Fittings

Drawers	1	1
Containers (150mm deep)	-	-

Electrical Data - Hydrocarbon Refrigerant

Refrigerant	R290	R290
Energy Efficiency Class	C	D
Energy Consumption (kW / 24hrs)	1.84	4.41
Start Up (Amps)	5.7	7.7
Running (Amps)	1.48	1.46
Heat Rejection	476	305

IMPORTANT NOTES:

*Energy consumption is tested to EN153 in 24hrs

**Heat rejection is evaporating at -10°C in 32°C Ambient

All refrigeration equipment requires adequate ventilation for efficient and effective performance.

Williams is committed to a policy of continual product development and innovation. As such, we reserve the right to change product specifications stated without prior notice.

Williams Refrigeration
Bryggen Road,
North Lynn Industrial Estate
King's Lynn, Norfolk. PE30 2HZ

T +44(0) 1553 817 000
Spares: +44(0) 1553 817 017
E info@williams-refrigeration.co.uk
W www.williams-refrigeration.co.uk

