

# FISH ZIRCON TECHNICAL DATASHEET

## FZ18 ZIRCON FISH CABINET



FZ18

Dimensions (mm)	External	Internal
Width	595	445
Depth	722	598
Height	1906	1250
Door Opening		1276
<b>Capacity</b>		
Capacity (kg)		114

### KEY FEATURES

- Foodsafe stainless steel exterior and interior
- CoolSmart controller
- Designed and engineered to operate efficiently up to a 43°C ambient
- Self closing doors
- Precision injected, high density 75mm polyurethane insulation
- Cabinet designed and fitted with low level heavy-duty, non-marking swivel castors with brakes to front
- Barrel locked doors
- 7 polypropylene containers, each with a removable slime tray
- Drained through the base into unit compartment exiting to rear - drain should be connected to a permanent waste or suitable container

### OPTIONS

- Bottom mounted refrigeration system
- 25mm adjustable levelling feet



# FISH ZIRCON TECHNICAL DATA

Fish Zircon	FZ18
Temperature (°C)	-2/+2
Power Supply	220V/240V 50Hz/1Ph
Fuse (Amps)	13
Defrost	Auto off-cycle
Noise Level (dBA)	50.0

## Fittings

Shelves	7 polypropylene trays
---------	-----------------------

## Electrical Data - Standard Refrigerant

Refrigerant	R134a
Energy Consumption (kW / 24hrs)*	2.21
Start Up (Amps)	12.6
Running (Amps)	5
Heat Rejection (kW / 24hrs)**	565

## IMPORTANT NOTES:

\*Energy consumption is tested to EN153 in 24hrs

\*\*Heat rejection is evaporating at -10°C in 32°C Ambient

All refrigeration equipment requires adequate ventilation for efficient and effective performance.

Williams is committed to a policy of continual product development and innovation. As such, we reserve the right to change product specifications stated without prior notice.

Williams Refrigeration  
Bryggen Road,  
North Lynn Industrial Estate  
King's Lynn, Norfolk. PE30 2HZ

T +44(0) 1553 817 000  
Spares: +44(0) 1553 817 017  
E info@williams-refrigeration.co.uk  
W www.williams-refrigeration.co.uk

