JADE REMOTE COUNTER TECHNICAL

DATASHEET

JC2R JADE TWO DOOR REMOTE COUNTER

JC3R JADE THREE DOOR REMOTE COUNTER



JC2R

Dimensions (mm)	External	Internal	
Width	1231	870	
Depth	700	585	
Height	887	600	
Door Opening		390	
Capacity			
Capacity cu.ft/ltrs	13.2/374		



JC3R

Dimensions (mm)	External	Internal
Width	1711	1350
Depth	700	585
Height	887	600
Door Opening		390
Capacity		
Capacity cu.ft/ltrs	19.2/545	

KEY FEATURES

- Foodsafe stainless steel exterior and aluminium interior
- Radiused, easy clean, interior based corners
- Self closing doors
- Barrel locked doors
- Magnetic balloon door gaskets with 100% tight seal
- Fitted with 2 of 1/1GN nylon coated wire shelves per section as standard or trayslides to accommodate 1/1GN containers
- Anti-tilt trayslides
- Removable racking system

- Precision injected, high density polyurethane insulation with low GWP (Global Warming Potential) and zero ODP (Ozone Depletion Potential).
- Adjustable stainless steel 304 legs with flange for deck fixing
- CoolSmart controller
- Designed and engineered to operate efficiently up to a 43°C ambient
- · High performance helium leak testing
- Connection to third party supervisory communication systems such as BMS is possible using proprietary equipment. Please contact Williams for more information.

OPTIONS

- Stainless steel interior
- · Additional shelving / trayslides
- Drawer banks (2 or 3)
- · Screw on splash-back



JADE REMOTE COUNTERS TECHNICAL DATA

	HIC2R	LIC2R	HIC3R	LIC3R		
Temperature (°C)	+1/+4°C	-18/-22°C	+1/+4°C	-18/-22°C		
Power Supply	230V/50Hz/1Ph					
Fuse (Amps)	13	13	13	13		
Defrost	Off-cycle	Electric	Off-cycle	Electric		
Fittings						
Shelves	4	4	6	6		
Trayslides per door	4	4	4	4		
Electrical / Energy Data - Standard Refi	rigerant					
Refrigerant	R134a	R452A	R134a	R452A		
Running (Amps)	0.5	0.5	0.5	0.5		
Required Refrigeration Capacity	320W*	335W**	320W*	335W**		

IMPORTANT NOTES:

*Evaporating at -10°C within a 32°C Ambient

**Evaporating at -30°C within a 32°C Ambient

Williams is committed to a policy of continual product development and innovation. As such, we reserve the right to change product specifications stated without prior notice.

Williams Refrigeration Bryggen Road, North Lynn Industrial Estate King's Lynn, Norfolk. PE30 2HZ

T +44(0) 1553 817 000 Spares: +44(0) 1553 817 017 E info@williams-refrigeration.co.uk W www.williams-refrigeration.co.uk





