OVERNIGHT THAW TECHNICAL DATASHEET

S10T-SS OVERNIGHT THAW



S1OT-SS

| Dimensions (mm) | External | Internal |
|------------------------|----------|----------|
| Width | 865 | 482 |
| Depth | 801 | 560 |
| Height | 1960 | 1370 |
| Door Opening | | 1524 |
| Capacity | | |
| Max load capacity (kg) | | 35 |

^{*}Per Section

KEY FEATURES

- Foodsafe stainless steel exterior and interior
- Easy to clean dished base with radiused corners
- CoolSmart controller
- Designed and engineered to operate efficiently up to a 43°C ambient
- Self closing door
- Precision injected, high density 75mm polyurethane insulation
- Heavy duty, non-marking swivel castors with brakes
- Barrel locked door
- Product does not exceed 3°C throughout the thawing process

- · Additional food can be placed in the cabinet with no detrimental effect on those products already inside
- · Anti-tilt trayslides
- Cooking thawed food is quicker and safer than cooking from frozen eliminating the risk of cold spots once cooking has finished
- Designed with forced air heating and cooling circuits which cycle alternatively keeping the food within the correct temperature range of 0°C to +3°C
- Connection to third party supervisory communication systems such as BMS is possible using proprietary equipment. Please contact Williams for more information.

OPTIONS

· Stainless steel back



www.williams-refrigeration.co.uk

OVERNIGHT THAW TECHNICAL DATA

| Overnight Thaw | S1OT-SS |
|--|---------------------|
| Temperature (°C) | 0/+4 |
| Power Supply | 220V/240V 50Hz/1Ph |
| Fuse (Amps) | 13 |
| Defrost | Automatic off cycle |
| Noise Level (dBA) | 59 |
| Fittings | |
| Shelves (427 x 550mm) | 7 |
| Electrical Data - Standard Refrigerant | |
| Refrigerant | R290 |
| Energy Consumption (kW / 24hrs)* | 4.3 |
| Start Up (Amps) | 6.6 |
| Running (Amps) | 5.4 |
| Heat Rejection (kW / 24hrs)** | 692 |

IMPORTANT NOTES:

*Energy consumption is tested to EN153 in 24hrs

**Heat rejection is evaporating at -10°C in 32°C Ambient

All refrigeration equipment requires adequate ventilation for efficient and effective performance.

Williams is committed to a policy of continual product development and innovation. As such, we reserve the right to change product specifications stated without prior notice.

Williams Refrigeration Bryggen Road, North Lynn Industrial Estate King's Lynn, Norfolk. PE30 2HZ

T +44(0) 1553 817 000 Spares: +44(0) 1553 817 017 E info@williams-refrigeration.co.uk W www.williams-refrigeration.co.uk





